



SMART CONTROLLER



HYPER-CONNECTED



EMPOWER YOUR DATA

## OPTIONS




Profinet



Ethernet IP



EtherCAT



Safety module PL-d

> Also available:

- Other busfield on demand
- Gravotrace™ software

## ACCESSORIES



Control panel



Industrial footswitch



Air filter



90° elbow connector

> Also available:

- Standard footswitch
- 19" rack version
- Workbench stand

TECHNICAL SPECIFICATIONS	Xcom P	Xcom m
Technology	Pneumatic	Electro-magnetic
Weight (kg)	2.7	3.1
Rated power (VA)	140	260
Power supply	100 - 240 VAC 50-60Hz	
Dimensions L x W x D (mm)	287 x 170 x 152	
Piloting axis number	4 (X, Y, Z, $\theta$ )	
Operating temperature (°C)	5 - 45	
Piloting mode	Autonomous or with PC software	
Marking area (mm)	From 50 x 20 to 200 x 80 (other on demand)	
Marking possibilities	Text, variables, dates, serial numbers, 2D codes, logos...	
Fonts	+10 fonts in dot by dot or continuous stroke: Unicode support, personalized font on demand	
Communication	Ethernet TCP/IP - RS232 - USB - 8 inputs / 4 on-off-control outputs Profinet - Ethernet IP - EtherCAT	
Piloting software	Embedded software T08 with color touchscreen - Free PC software	

